



DigiSender® HQ²

TWIN INPUT 5.8GHz WIRELESS AV SENDER
Model: DG258



About AEI

Introduction to
DigiSenders

2.4GHz Analogue
Series

5.8GHz Analogue
Series

Digital Series

High Definition Series

iMedia™ Series

Wirefree Cables

Price List

Corporate Sales

DX2000-LCD

DG158

DG188-S

DG258

DG258-2RX

DG458

Contact Us:

Web: www.aei.eu

Email: sales@aei.eu

Tel: 02071 931 413

Fax: 01797 227 122



The DG258 is a 5.8GHz version of the DG200, our most successful DigiSender® ever. The Transmitter features two DigiConnector™ inputs allowing you to simultaneously connect two sources, such as your Satellite receiver and DVD recorder.

Switch inputs using the supplied DigiSender® Remote Control or with the button on the front of either the Transmitter or Receiver.

Features

- 5.8GHz Operating Frequency
- No interference from 2.4GHz Devices like Wi-Fi & Bluetooth
- Sleek Piano Black Design
- DigiConnector™ SCART Inputs
- Stunning DVD Quality Video
- Crystal Clear Hi-Fi Stereo Sound
- DigiEye™ Remote Relay Technology (IrDA, RC5/6)
- IR Systeme Technik™ Remote Relay Kit
- Widescreen Compatible
- Works Through Walls & Ceilings
- Fitted In Minutes
- Additional Receivers available

Packaging & Shipping Information

- Retail Packaging Dimensions: L: 205mm, W: 290mm, H: 60mm
- Retail Packaging Weight: 0.91kg
- Shipping Carton Dimensions: L: 630mm, W: 220mm, H: 310mm
- Shipping Carton Weight: 9.8kg
- Units per Carton: 10

Specifications

- Transmitter Inputs: 2x DigiConnector™ SCART
- Receiver Outputs: 1x SCART
- Audio/Video Frequency: 5.725GHz ~ 5.875GHz
- Audio/Video Channels: 4
- Remote Relay Frequency: 433MHz
- Remote Relay Channels: 4
- Remote Control Compatibility: IrDA, RC5, RC6
- Video Input Level: 1V Peak-Peak 75Ω
- Video Input Colour: PAL
- Audio Input Level: 1V PP Mod 1KHz, Dev 15KHz
- Audio Bandwidth: 20Hz-22KHz (-3dB)
- Sensitivity: -90dB
- Antenna: External
- Range: 100m (Clear Line of Sight)
- Power Supplies: 9VDC 300mA
- Dimensions: L: 90mm, W: 140mm, H: 25mm
- Weight: 0.3kg

